

STANDARD 2022 A



TECHNICAL SPECIFICATIONS

LENGTH OVERALL	11.96 m 39'3'' ft
HULL LENGTH	11.96 m 39'3'' ft
LENGTH AT WATERLINE	11.26 m 36'11'' ft
BEAM MAX	3.87 m 12'8" ft
DRAFT (standard) DRAFT (option)	2.40 m 7'10" ft 2.20 m 7'3" ft 2.40 m 7'10" ft (composit) 1.95m 6'4" ft *
LIGHT DISPLACEMENT (mLCC)	7,767 kg 17,123 lbs
BALLAST (standard)	2,700 kg 5,952 lbs
WATER CAPACITY	277 liters 73 US gal
FUEL CAPACITY	132 liters 34 US gal

ENGINE (standard)	28 kW / 38 HP Volvo Penta
ENGINE OCEANVOLT (option)	10 kW Oceanvolt electric
	15 kW Oceanvolt electric
AIR DRAFT (incl. antenna)	19.75 m 64'10'' ft
MAINSAIL	52.16 m ² 561'4'' sq ft
JIB	38.77 m² 417'3'' sq ft
GENNAKER	135.00 m² 1453'1" sq ft
I	15.92 m 52'3'' ft
J	4.50 m 14'9'' ft
Р	15.75 m 51'8'' ft
E	5.52 m 18'1" ft
BOAT DESIGN CATEGORY CE	A
DESIGN	Humphreys Yacht Design
	& Elan Design Team

STANDARD EQUIPMENT

CERTIFICATION

The ELAN E5 is delivered with a CE certificate and meets the requirements of European directive 2013/53/EU for recreational craft. The CE class A category certificate (unlimited Ocean voyages) is issued by Germanischer Lloyd.

HULL

Laminated with VAIL - Vacuum Assisted Infusion Lamination technology, to considerably improve strength, mechanical and chemical properties of the hull. High quality materials, SVG gelcoat for optimal chemical resistance against osmosis and mirror finish, sandwich construction using multi-directional fibreglass, structural closed cells foam core and single skin on loaded areas, vinyl ester skin coat and Isophtalic polyester resin are used for high quality product. Powerful inner structure distributes all loads from the keel and rig effectively with a minimum flexing of the hull.

DECK

- Sandwich hand lamination construction using multi-directional fibreglass and Balsa core, moulded anti slip surface on deck and coach roof
- Teak on cockpit seats
- Garage with instrument pod

KEEL

• 2,40m draft performance cast iron T shape keel

INTERIOF

 Interior is built with Natural Oak veneered plywood, laminated floorboards Tobbacco style

SALOON

- Saloon table
- U shape saloon seating
- Custom deck port lights
- 2 flush deck escape hatch
- · Lockers and shelves above backrests along the hull on both sides,
- Overhead LED lights
- Curtains over portlights and blinds over hatch
- 2 hull portlights

GALLEY

- L-shaped galley
- Front opening refrigerator 65 L
- S/S gas cooker with 3 rings and oven
- Double S/S sink with tap and pressurised water system
- Cooker and sink covers
- Lockers, cupboards and drawers
- Opening portlight above galley
- Overhead LED light, LED light over the worktop
- Curtains over portlights
- Acrylic water protector

HEAD / SHOWER COMPARTMENT

- Marine toilet
- Washbasin with pressurised tap
- Storage locker under the sink
- Locker with mirror
- Electric shower drain pump
- Wet locker inside shower compartment
- Separate shower compartment with acrylic water protection
- Overhead LED lights
- Opening flush deck hatch
- Opening portlight
- Curtains over portlights

NAVIGATION STATION

- Pivoting chart table
- Reading LED spotlight
- Shelves and lockers below portlight
- USB socket inside (1 pcs)

FORWARD CABIN

- Double berth
- 2 lateral stowage shelves
- Port and starboard lockers
- Drawers and stowage under berth 2 reading LED lights with USB
- Overhead LED light
- Flush deck escape hatch with blind
- Two flush hatches

AFT CABINS

- 2 identical double berth cabins
- Double berth
- Storage under the berth
- 2 lateral storage shelves
- Storage locker
- 2 reading LED lights with USB
- Overhead LED light
- Flush opening deck hatch per cabin and 2 opening portlights per cabin
- · Curtains over portlights

MAST / STANDING RIGGING

- Selden tapered keel stepped performance aluminium anodised fractional mast profile with 2 sets of aft swept spreaders and aluminium single line reefing boom with rigid vang
- Genoa furling system Selden Furlex 300TD
- Windex
- Stainless steel standing rigging 1/19
- Mechanical backstay tensioner (hasselforce)
- · Deck light

RUNNING RIGGING

- · Main halyard, jib halyard, gennaker halyard
- Main sheet T system, 2 jib sheets 2 gennaker sheets
- Gennaker retriever
- Outhaul for the main, 2 reefing lines
- Toping lift

DECK EQUIPMENT

- 2 halyard winches on coach roof Harken B40.2
- 2 genoa winches Harken B46.2
- 2 main sail winches Harken B40..2
- Harken mainsheet track recessed in the cockpit floor with T mainsheet system
- · 2 jib sheets tracks with cars adjustable from cockpit
- 2 deck organisers
- 2 sets of clutches Spinlock
- Gennaker deck gear with carbon retractable gennaker pole
- Steering compass
- 2 white composite steering wheels
- S/S Pulpits, pushpits and stanchions with 2 lifelines
- Bow anchor fitting removable S/S 6 Retractable mooring cleats
- Winch handle pocket
- Cockpit locker on port and starboard side
- Gas bottle locker draining outboard
- S/S bathing ladder, grab rails on coach roof
- · Removable cockpit table

ENGINE EQUIPMENT

- D2-40 Volvo Penta, S-Drive, S/S engine control lever in cockpit and engine control panel
- Fuel tank fuel filter with water separator
- 2 blade Flex-o-fold folding propeller

WATER SYSTEM

- Fresh water tanks 277 I
- Black water tank 70 I
- 12 V fresh water pressure pump
- Central 12V bilge pump with automatic switchHot water system incl. hot water shower in cockpit
- Hand bilge pump in cockpit

ELECTRICAL SYSTEM

- 12 V control panel with voltmeter for batteries, fresh water and fuel level indicator
- Shore connection installation with 15m shore power cable 230V
- Battery charger 12V-40A
- Inverter 350 VA on single socket
- Cockpit led lights
- Courtesy lights in companionway
- 3 separate 12V AGM batteries (95Ah engine battery and 2 95Ah service battery)
- Navigation lights according to Col Reg
- Double IP67 USB socket and 12v socket in cockpit

- 30 mbar pressure relief valve with a shut-off valve
- Gas bottle ALU EU standard; UNP 2kg/4,8l only for EU

MISCELLANEOUS

- 2 winch handles
- 2 fire extinguishers
- Flag pole

All published data and allowed tolerances according to EN ISO 86766, E&O