

STANDARD 2023 A

TECHNICAL SPECIFICATIONS

LENGTH OVERALL	15,30 m 50' 2'' ft
HULL LENGTH	14,10 m 46' 3'' ft
LENGTH AT WATERLINE	13,68 m 44' 11'' ft
BEAM MAX	4,49 m 14' 9'' ft
DRAFT (standard) DRAFT (option)	2,80 m 9' 2'' ft (not mounted) 2,40 m 7' 10'' ft (not mounted) 2,95 m 9' 8'' ft (not mounted)
STD DISPLACEMENT	11.250 kg 24.802,00 lbs
STD DISPLACEMENT BALLAST (standard)	11.250 kg 24.802,00 lbs 3.267 kg 7.202 lbs
BALLAST (standard)	3.267 kg 7.202 lbs

AIR DRAFT (incl. antenna)	23,26 m 76' 4'' ft
MAINSAIL	68,56 m2 738' sq ft
JIB	53,71 m2 578' sq ft
GENNAKER	201,7 m2 2171' sq ft
I	19,04 m 62' 6'' ft
J	5,37 m 17' 4'' ft
Р	18,30 m 60' ft
E	6,31 m 20' 8'' ft
BOAT DESIGN CATEGORY CE	A
EXTERIOR AND INTERIOR DESIGN NAVAL ARCHITECT:	Pininfarina Humphreys Yacht Design

STANDARD EQUIPMENT

CERTIFICATION

The ELAN GT6 is delivered with A CE certificate and meets the requirements of European directive 2013/53/EU for recreational craft.

HULL

Laminated with 3D VAIL - Vacuum Assisted Infusion Lamination technology, to considerably improve strength, mechanical and chemical properties of the hull. High quality materials, SVG gelocat and vinyl ester skin coat for optimal chemical resistance against osmosis and mirror finish, sandwich construction using multi-directional fibreglass, structural closed cells foam core and single skin on loaded areas, vinyl ester skin coat and Isophthalic polyester resin are used for high quality product. Powerful inner structure distributes all loads from the keel and rig effectively with a minimum flexing of the hull.

DECK

- Sandwich laminated with VAIL (Vacuum Assisted Infusion Lamination) technology with sandwich construction to assure stiffness as well as thermal and sound insulation. Anti slip surface is moulded on deck, cockpit and coach roof.
- Synthetic teak is included on swim platform when ordered as an option.

KEEL

• 2,8 m draft performance cast iron T shape keel, dry fitted, not mounted.

INTERIOR

Interior is built with Natural Oak veneered plywood, laminated floorboards.

SALOON

- · Fixed saloon table
- U shape saloon seating
- · Custom deck port lights
- Custom hull port lights
- Flush deck escape hatch
- Flush deck hatch
- · Lockers and shelves above backrests along the hull on both sides
- Overhead LED lights
- Curtains over portlights and blinds over hatchesReading LED lights with USB

GALLEY

- L-shaped galley on stb sideLockers, cupboards and drawers
- S/S gas cooker with 2 rings and oven
- Overhead LED light,
- Cooker and sink covers
- Front opening refrigerator 130 I
 S/S sink double with tap and pressure of the second seco
- S/S sink double with tap and pressurised water system
- Flush deck hatchCustom deck port lights
- Curtains over portlights



STANDARD PRICE 429.900,00 €



HEAD / SHOWER COMPARTMENT

- Marine toilet
- Washbasin with pressurised tap
- ٠ Storage locker under the sink
- Mirror
- Electric shower drain pump
- Overhead LED lights Curtains over portlights
- Separate shower compartment
- · Flush deck hatch

NAVIGATION STATION

- · Pivoting chart table
- Red ceiling LED light
- Shelves and lockers below portlight
- USB socket inside
- 230V socket

FORWARD CABIN

- Double island berth
- 2 lateral storage shelves
- Port and starboard lockers
- Storage under berth
- Reading LED lights with USB Overhead LED lights
- Flush deck escape hatch with blind
- Flush hatch with blind
- Custom deck port light
- Custom hull port lights
- Storage locker

AFT CABINS

- Large aft cabin with cushioned backrest feature
 Double berth
- Storage under the berth
- Lateral storage shelve Storage locker
- Reading LED light with USB
- Overhead LED light
- Flush opening deck hatch and opening portlight
- Custom hull portlight
- Curtains over portlights and blinds over hatches

HEAD / SHOWER COMPARTMENT FRONT CABIN

- Marine toilet
- Washbasin with pressurised tap Storage locker under the sink
- •
- Mirror
- Electric shower drain pump
- Overhead LED lights ٠ Curtains over portlights ٠
- Separate shower compartment
- · Flush hatch with blind
- Custom deck port light .

MAST / STANDING RIGGING

- Selden tapered keel stepped performance aluminium anodised fractional mast profile with 2 sets of aft swept spreaders and aluminium single line reefing boom with rigid vang
- Genoa furling system Selden TD Furlex
- Windex
- Stainless steel standing rigging 1/19
- Mechanical backstay tensione
- Deck light Anchor light

RUNNING RIGGING

- Main halyard, jib halyard and gennaker halyard
- Main sheet T system, 2 jib sheets, gennaker sheets
- Outhaul for the main, 2 reefing lines
- Topping lift
- · Gennaker retriever

DECK EQUIPMENT

- 2 halyard winches on coach roof Harken 46.2 radial
- 2 main sail winches Harken 50.2 radial
- 2 genoa winches Harken 60.2 radial
- Harken mainsheet track recessed in the cockpit floor with T mainsheet system
- 2 jib sheets tracks with cars adjustable from cockpit
- 2 sets of deck organisers 2 sets of clutches Spinlock
- Fixed carbon bowsprit
- Steering compass
- Grab rail around steering pedestal 2 white composite steering wheels
- S/S Pulpits, pushpits with 2 lifelines
- Bow anchor fitting S/S
- 6 x Retractable mooring cleats
- Cockpit locker on port and starboard side
- Wet locker in cockpit floor
- Rope storage on port and starboard side Sail locker
- Gas bottle locker draining outboard S/S bathing ladder
- · Grab rails on coach roof

ENGINE EQUIPMENT

- · Yanmar 4JH57 S-Drive, engine control lever in cockpit and engine control panel
- Fuel tank 240 I with fuel filter and water separator
- 3 blade folding propeller

WATER SYSTEM

- Fresh water tank 370 I
- Black water tank 2x70 l
- 12 V fresh water pressure pump
- Central 12 V bilge pump with automatic switch Hot water system incl. hot water shower in cockpit
- Hand bilge pump in cockpit

ELECTRICAL SYSTEM

- 12 V control panel with voltmeter for batteries, fresh water and fuel level indicator
- Battery monitor

GAS SYSTEM

MISCELLANEOUS

2 winch handles

Flag pole

Elan, d.o.o. | Marine Division | Begunje 1, 4275 Begunje na Gorenjskem, Slovenia | +386 4 53 51 109 | sail@elan.si | www.elan-yachts.com

· 2 fire extinguishers

All published data are preliminary.

- Inverter 350 VA
- Cockpit LED lights
- Courtesy lights in companionway

Navigation lights according to Col Reg

- Shore connection installation with 25m shore power cable 230 V Battery charger 12 V-40 A
- 3 separate 12 V AGM batteries (90Ah engine battery and 2x140 Ah service battery)
- Double IP 67 USB socket and 12 V socket in cockpit

Gas bottle ALU – EU standard; UNP 2kg/4,8l only for EU

• 30 mbar pressure relief valve with a shut-off valve